



BATTISTELLA GIOSUÈ E GIULIANO SRL

## Tondo per cemento armato

Sezione in cm<sup>2</sup> per numero di barre



Diametro mm	Peso kg/m	Numero barre										
		1	2	3	4	5	6	7	8	9	10	12
		sezione cm <sup>2</sup>										
6	0,222	0,28	0,57	0,85	1,13	1,41	1,70	1,98	2,26	2,54	2,83	3,39
8	0,395	0,50	1,01	1,51	2,01	2,51	3,02	3,52	4,02	4,52	5,03	6,03
10	0,617	0,79	1,57	2,36	3,14	3,93	4,71	5,50	6,28	7,07	7,85	9,42
12	0,888	1,13	2,26	3,39	4,52	5,65	6,79	7,92	9,05	10,18	11,31	13,57
14	1,208	1,54	3,08	4,62	6,16	7,70	9,24	10,78	12,32	13,85	15,39	18,47
16	1,578	2,01	4,02	6,03	8,04	10,05	12,06	14,07	16,08	18,10	20,11	24,13
18	1,998	2,54	5,09	7,63	10,18	12,72	15,27	17,81	20,36	22,90	25,45	30,54
20	2,466	3,14	6,28	9,42	12,57	15,71	18,85	21,99	25,13	28,27	31,42	37,70
22	2,984	3,80	7,60	11,40	15,21	19,01	22,81	26,61	30,41	34,21	38,01	45,62
24	3,551	4,52	9,05	13,57	18,10	22,62	27,14	31,67	36,19	40,72	45,24	54,29
25	3,853	4,91	9,82	14,73	19,63	24,54	29,45	34,36	39,27	44,18	49,09	58,90
26	4,168	5,31	10,62	15,93	21,24	26,55	31,86	37,17	42,47	47,78	53,09	63,71
28	4,834	6,16	12,32	18,47	24,63	30,79	36,95	43,10	49,26	55,42	61,58	73,89
30	5,549	7,07	14,14	21,21	28,27	35,34	42,41	49,48	56,55	63,62	70,69	84,82
32	6,313	8,04	16,08	24,13	32,17	40,21	48,25	56,30	64,34	72,38	80,42	96,51